

# Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### MARHWH Maestro Accessory Dimmer White Clam

aestro Companion Dimmer For Multi-Location Use, 120V, Gloss hish, Clamshell Packaging In White 2000 (Ibs/each) hting Dimmers hite hite Diss AESTRO ACCESSORY DIMMER WHITE CLAM T MA-RH-WH MAESTRO REMOTE WHITE C
hish, Clamshell Packaging In White 2000 (lbs/each) hting Dimmers histic/Metal s hite biss
2000 (lbs/each) hting Dimmers hstic/Metal s hite hite hite hite hite
hting Dimmers Istic/Metal s hite Dss AESTRO ACCESSORY DIMMER WHITE CLAM
s nite oss AESTRO ACCESSORY DIMMER WHITE CLAM
s nite oss AESTRO ACCESSORY DIMMER WHITE CLAM
nite oss AESTRO ACCESSORY DIMMER WHITE CLAM
AESTRO ACCESSORY DIMMER WHITE CLAM
aestro accessory dimmer white clam
aestro accessory dimmer white clam
AESTRO ACCESSORY DIMMER WHITE CLAM
T MA-RH-WH MAESTRO REMOTE WHITE C
r Use with Maestro Multi-Location dimmer switches only. mpanion dimmer switches allow you to dim from either end o allway. Use up to nine companion dimmers with only one aestro Multi-Location dimmer switch. Coordinating Claro wall ites and accessories sold separately.
aestro Companion dimmer for multi-location use, 120V, Gloss ish, clamshell packaging in white
aestro Remote White CLM
r true multi-location dimming from every location; use up to ne companion dimmers with only one Maestro multi-location nmer. Use standard 3-way wiring. 120V
tron
027557708418
A-RH-WH
7557708418
2     

Category Description	Residential dimmers, motion sensors, controls, & photo cells
Туре	Companion dimmer, clamshell packaging



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

#### Packaging

Carton	1
Package	3
Weight Per each	0.2

#### Uses, Certifications, and Standards

josi (incations), and standards		
Application	Lighting Control	
Enclosure	Plastic	
Mounting	WALLBOX	
Operating Temperature	32 to 104	
standard	UL, CSA, NOM, FCC, IC, ISO 9001	