

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



N2 #2 STR Cu Split Bolt *Nsi Industries*

| a contract of the contract of | |
|---|--|
| Catalog Number | N2 |
| Manufacturer | Nsi Industries |
| Description | Split Bolt Connector, #6 Awg (Range Of Equal Main and Tap-Solid Conductor Size, #2 Awg (Range Of Equal Main and Tap-Stranded);#14 Awg (Minimum Tap With One Maximum Main-Stranded) Conductor Size, Non-Insulated, Copper;Copperweld Conductor Material, 2 Conductors, +90 °C Operating Temperature, 1.153 In Overall Length, Split Terminal, 600 V, 0.13 LB/Ea |
| Weight per unit | 0.1300 (lbs/each) |
| Product Category | Lorgo Torminals & Connectors |
| Features | |
| Material | Copper |
| Number of Conductors | 2 |
| Poles | 1 |
| Voltage Rating | 600 V |
| Warranty | |
| Wire Size | 6 SOL - 2 STR |
| Wire Type | Class A & B |
| Material, Color, and Finish | |
| Color | Copper |
| Finish | COPPER |
| Dimensions and Weight | |
| Size | L=1.153 - W=.748 |
| Descriptions | |
| Description | #2 STR CU SPLIT BOLT |
| extra long description | NSI N-2 Split Bolt Copper 2 |
| Features | Copper Split Bolt Connector 2 AWG Copper Split Bolt Connectors are high-strength solderless service connectors made of high-copper alloy for copper and copperweld wires. Type for two maximum wire sizes. |
| Manufacturer Information | |
| GTIN | 00662381020055 |
| UPC | 662381020055 |
| | |



standard

Temperature Rating

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Taxonomies, Classifications, and Categories | | | |
|---|--------------------|--|--|
| Category Description | SPLIT BOLTS | | |
| Туре | Copper Split Bolts | | |
| Packaging | | | |
| Carton | 1 | | |
| Package | 40 | | |
| Weight Per each | 0.13 | | |
| Uses, Certifications, and Standar | ds | | |
| Application | Wire Termination | | |
| environmental conditions | 90 C | | |

UL486B

90 C