

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### N30 3/0 Cu Split Bolt

Nsi Industries	ort .			
Catalog Number	N30			
Manufacturer	Nsi Industries			
Description	Copper Split Bolt Connector 3/0 Awg Copper Split Bolt			
	Connectors Are High-Strength Solderless Service Connectors			
	Made Of High-Copper Alloy For Copper and Copperweld Wires.			
	Type For Two Maximum Wire Sizes.			
Weight per unit				
Product Category	Large Terminals & Connectors			
Features				
Material	• •			
Number of Conductors	2			
Poles	1			
Voltage Rating				
Warranty				
Wire Size				
Wire Type	Class A & B			
Material, Color, and Finish				
Color	Copper			
Finish	COPPER			
Dimensions and Weight				
Size	L=2.007 - W=1.102			
Descriptions				
Description	3/0 CU SPLIT BOLT			
extra long description	NSI N-3/0 Split Bolt Copper 3/0			
Features	Copper Split Bolt Connector 3/0 AWG Copper Split Bolt			
	Connectors are high-strength solderless service connectors made			
	of high-copper alloy for copper and copperweld wires. Type for			
	two maximum wire sizes.			
Long Description	Copper Split Bolt Connector 3/0 AWG Copper Split Bolt			
	Connectors are high-strength solderless service connectors made			
	of high-copper alloy for copper and copperweld wires. Type for			
	two maximum wire sizes.			
Product Type	Split Bolt Copper 3/0			
Special Features	2 SOL-3/0 STR - 10 Pack			



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

и		_		1		_ 1				<b>.</b>					_
ľ	۱ <i>۱</i>	12	n		-	СТ		·Δr	ın	TO	۱rr	ทว	TI	n	<b>7</b>
	v			u	а	L.I	uı	<b>CI</b>	'In	H.V.	,, ,	па		u	

Brand	NSi
GTIN	00662381020086
Manufacturers Part Number	N-3/0
UPC	662381020086

#### **Taxonomies, Classifications, and Categories**

Category Description	SPLIT BOLTS
Туре	Copper Split Bolts

#### **Packaging**

J		
Carton	1	
Package	10	
Weight Per each	0.43	

#### Uses, Certifications, and Standards

Application	Wire Termination
environmental conditions	90 C
standard	UL486A
Temperature Rating	90 C