

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

NL300 225A Neutral Lug For A 300 MCM Max. Wire Size $\it Eaton\ Corp$

| Catalog Number | NL300 |
|------------------------------------|--|
| Manufacturer | Eaton Corp |
| Description | Eaton CH 3/4-Inch Loadcenter and Breaker Accessories - Neutral Lug, Neutral Lug, 225 A, CH, 0.75 In, #300 Kcmil Max Wire Size |
| Weight per unit | 0.1000 (lbs/each) |
| Product Category | Load Center Accessories |
| Features | |
| amperage rating | 225 |
| interrupt rating | 10 |
| Phase | 1 |
| Dimensions and Weight | |
| Depth | 8 |
| Height | 0.1 |
| Width | 5 |
| Descriptions | |
| Description | 225A NEUTRAL LUG FOR A 300 MCM MAX. WIRE SIZE |
| extra long description | ETN NL300 225A Neutral Lug For a 30 |
| Features | Specially designed for easy installation, Eaton's BR 1-inch load centers house the branch circuit breakers and the wiring require to distribute power to individual circuits. They serve as main breaker for service entrances or as main lug when adding circuits to existing service. The main breaker protects the entire panel and can be used as a service disconnect. The branch breakers protect the wires leading to individual electrical loads such as fixtures and outlets. |
| Long Description | Eaton CH 3/4-inch Loadcenter and Breaker Accessories - Neutral Lug, Neutral lug, 225 A, CH, 0.75 in, #300 kcmil max wire size |
| Product Type | 225A Neutral Lug For A 300 MCM Max Wire |
| Manufacturer Information | |
| Brand | Eaton |
| GTIN | 00782113099170 |
| Manufacturers Part Number | NL300 |
| UPC | 782113099170 |
| Taxonomies, Classifications, and (| Categories |
| Category Description | LOADCENTER ACCESSORIES |
| T | A |

Accessory



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | |
|-------------------------------------|--------|
| Carton | 1 |
| Weight Per each | 0.1 |
| Uses, Certifications, and Standards | |
| Application | Other |
| standard | UL 489 |