

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PSG120E PWR Supply-1PH 90-264VAC 24VDC@5a Eaton Corp

PSG120E
Eaton Corp
Power Supply, 120W, Single-Phase, 100-240V Input Voltage, 24 VDC ± 2% Output Voltage, 1.4A Input Current, 5A Output Current, Less Than 80A Inrush Current, 47-63 HZ, 85-264V, 120-375 VDC, Aluminum Enclosure, Heavy-Duty Screw Terminals
1.7 (lbs/each)
Ac Power Supplies
4.7600 IN X 1.9700 IN X 4.5300 IN
Aluminum
Yes
Single-phase
85-264 Vac, 100-375 Vdc
120W
PWR SUPPLY-1PH 90-264VAC 24VDC@5A
ETN PSG120E Power Supply-1ph 90-264
The PSG line of general purpose power supplies is used in a wide variety of industrial control applications. Applications include communication networks, sensors, PLCs and many other electrical systems. Each model is equipped with the options of a rugged metal or plastic housing, heavy-duty screw or finger-safe terminals and a variety of protection features. The PSG line offers the flexibility of operating with a universal input voltage of 100–240 Vac. It also provides system protection and continuous oper
Power Supply, 120W, Single-phase, 100-240V input voltage, 24 Vdc ± 2% output voltage, 1.4A input current, 5A output current, less than 80A inrush current, 47-63 Hz, 85-264V, 120-375 Vdc, Aluminum enclosure, Heavy-duty screw terminals
Power Supply-1PH 90-264VAC, 24VDC@5a
Varistor transient surge voltage, surge voltage protection against internal surge, safety class 1 with ground connection, finger-safe cover



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Eaton
GTIN	00786685215440
Manufacturers Part Number	PSG120E
UPC	786685215440

Taxonomies, Classifications, and Categories

Туре	General purpose power supply	
Packaging	1	
Carton		
Weight Per each	1.7299	

Uses, Certifications, and Standards

Application	Commercial / Institutional Buildings / Structures - Power
	Distribution and Controls
Frequency Rating	47-63 Hz
standard	cULus/UL 60950-1,cUL Certified,IEC Rated,EN Listed,CSA
	Certified,UL 508,CE Marked,German Safety,RoHS Compliant