

Eaton PSG60F24RM

Catalog Number: PSG60F24RM

Eaton PSG series Power Supply, Aluminum, 320-575 Vac, 47-63 Hz, Finger-safe terminals, 24 Vdc output, Three-phase, 960W output power, -25°C-75°C operating temp



General specifications

| | |
|--|-----------------------|
| Product Name | Catalog Number |
| Eaton PSG general purpose power supply | PSG60F24RM |
| | UPC |
| | 786685683577 |
| Product Length/Depth | Product Height |
| 7 in | 3 in |
| Product Width | Product Weight |
| 6.5 in | 4 lb |
| Warranty | Compliances |
| 3 year | RoHS Compliant |
| | CE Marked |

Certifications
UL 508
IEC Rated
CSA Std. C22.2
EN Listed

Product specifications

Operating temperature - max

75 °C

Operating temperature - min

-25 °C

Phase

Three-phase

Frequency rating

47-63 Hz

Enclosure color

Aluminum

Output voltage

24 V

Terminals

Finger-safe

Input voltage

320-575 Vac

Output

960 W

Resources

Brochures

[Eaton's PSG Series Power Supplies](#)

Installation instructions

[Installation Instructions for PSG60F Power Supply](#)

Multimedia

[How to size and select a Power Supply](#)

Specifications and datasheets

[Eaton Specification Sheet - PSG60F24RM](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)

Eaton PSG60F24RM

Catalog Number: PSG60F24RM

Eaton PSG series Power Supply, Aluminum, 320-575 Vac, 47-63 Hz, Finger-safe terminals, 24 Vdc output, Three-phase, 960W output power, -25°C-75°C operating temp



General specifications

| | |
|--|-----------------------|
| Product Name | Catalog Number |
| Eaton PSG general purpose power supply | PSG60F24RM |
| | UPC |
| | 786685683577 |
| Product Length/Depth | Product Height |
| 7 in | 3 in |
| Product Width | Product Weight |
| 6.5 in | 4 lb |
| Warranty | Compliances |
| 3 year | RoHS Compliant |
| | CE Marked |

Certifications

UL 508
IEC Rated
CSA Std. C22.2
EN Listed

Product specifications

Operating temperature - max

75 °C

Operating temperature - min

-25 °C

Phase

Three-phase

Frequency rating

47-63 Hz

Enclosure color

Aluminum

Output voltage

24 V

Terminals

Finger-safe

Input voltage

320-575 Vac

Output

960 W

Resources

Brochures

[Eaton's PSG Series Power Supplies](#)

Installation instructions

[Installation Instructions for PSG60F Power Supply](#)

Multimedia

[How to size and select a Power Supply](#)

Specifications and datasheets

[Eaton Specification Sheet - PSG60F24RM](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)