

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PT300 #300 Pin Terminal Nsi Industries

Catalog Number	PT300
Manufacturer	Nsi Industries
Description	Stranded Bi-Metallic Pin Terminal 300 MCM Stranded Bi-Metallic
	Pin Terminals Is Designed to Facilitate Termination Of Aluminum
	Conductors. Tin-Plated Stranded Copper Pin. Connector Bores
	Are Coated With Oxide Inhibitor. Supplied With Epdm Insulating
	Cover. UI 486B Listed. Rated 600 Volts.
Weight per unit	
Product Category	Large Terminals & Connectors
Features	
connection	4/0 Pin
insulation	Plastisol Cover
Material	Aluminum - Tin Plated Copper Pin
Number of Conductors	1
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR
Material, Color, and Finish	
Color	Brown
Finish	Aluminum
Dimensions and Weight	
Size	L=4.08 - OD=1.16 - ID=.653 - Pin Dia=.523
Descriptions	
Description	#300 PIN TERMINAL
extra long description	NSI PT300 Aluminum Pin Terminal Cu
Features	Stranded Bi-Metallic Pin Terminal 300 MCM Stranded Bi-Metallic
	Pin Terminals is designed to facilitate termination of aluminum
	conductors. Tin-plated stranded copper pin. Connector bores are
	coated with oxide inhibitor. Supplied with EPDM insulating cover.
	UL 486B listed. Rated 600 volts.
Long Description	Stranded Bi-Metallic Pin Terminal 300 MCM Stranded Bi-Metallic
	Pin Terminals is designed to facilitate termination of aluminum
	conductors. Tin-plated stranded copper pin. Connector bores are
	coated with oxide inhibitor. Supplied with EPDM insulating cover.
	UL 486B listed. Rated 600 volts.
Product Type	
Special Features	300 MCM (STR) - 4/0 CU Pin Size



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Information

Brand	NSi
GTIN	00662381033093
Manufacturers Part Number	PT300
UPC	662381033093
Taxonomies, Classifications, and Categories	
Category Description	TERMINALS
Туре	Bi-Metallic Pin
Packaging	
Carton	1
Weight Per each	0.42
Uses, Certifications, and Standards	
Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B
Temperature Rating	90 C