

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

DTDA4CTD 00 Dogroo 4" DT Conn

PIRA6SIR 90 D Pass & Seymour/Leg	grand	
Catalog Number	PTRA6STR	
Manufacturer	Pass & Seymour/Legrand	
Description	Plugtail Registered Connectors, Right Angle, Stranded, 6-Inch Plugtail Registered Devices and Connectors Mean That Device Installation Is The Same Regardless Of Skill Level Of The Installer. The UI-Listed Connectors Are Keyed to Ensure Proper Wiring Installation Into Each Receptacle.	
Weight per unit	0.0687 (lbs/each)	
Product Category	Outlets, Jacks, & Plates	
Features		
Dielectric Strength	Withstands 2000V minimum	
media	Yes	
Number of Wires	3	
Poles	2	
Wattage	Electrical power is expressed in Amps and Volts.	
Wire Size	12 AWG	

Material, Color, and Finish

Color	White
Finish	Matte

Dimensions and Weight

	J
Size	7.5

Descriptions

Description	90 DEGREE 6" PT CONN
extra long description	P&S PTRA6STR 90 DEGREE 6 IN PT CONN
Long Description	PlugTail Registered Connectors, Right Angle, Stranded, 6-inch PlugTail Registered devices and connectors mean that device installation is the same regardless of skill level of the installer. The UL-Listed connectors are keyed to ensure proper wiring installation into each receptacle.
Product Type	90 Degree 6 In PT Connector
Special Features	Ultrasonically welded polycarbonate connector housing secures terminations and conductors in a UL Listed, finger safe housing. Large brass contacts snugly terminate on device blade terminals. Pre-stripped connector leads fasten to conductors, easier than standard pigtails. Exclusive patented feature, circuit label on back allows permanent circuit identification.



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Informa	ation	
----------------------	-------	--

Brand	Pass and Seymour	
GTIN	00785007044546	
Manufacturers Part Number	PTRA6-STR	
UPC	785007044546	

Taxonomies, Classifications, and Categories

Category Description	Commercial receptacles
Type	PlugTail™ Connector - Right Angle

Packaging

···-g···g		
Carton	1	
Package	250	
Weight Per each	0.0687	

Uses, Certifications, and Standards

Application Commercial	
environmental conditions Flammability: UL94 V2	
Mounting Device, Wall	
standard CULUS, UL, cULus UL498	
Temperature Rating -40° - 60° C	