

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



PTS350 350 Pin Terminal

Nsi Industries	Cillilla
Catalog Number	PTS350
Manufacturer	Nsi Industries
Description	Solid Pin Terminal For Copper and Aluminum Conductors 350 MCM All-Aluminum Pin Terminals Is Designed For Termination Of Both Aluminum and Copper Conductors. The Solid Pin Is Made Of Aluminum and Is Tin-Plated and Pre-Filled With Oxide Inhibitor. A Cover Is Provided For Quick Installation. Rated 600 Volts.
Weight per unit	0.1600 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
connection	250 Pin
insulation	Plastisol Cover
Material	Aluminum
Number of Conductors	1
Poles	1
Voltage Rating	600 V
Warranty	1 YEAR
Material, Color, and Finish	
Color	Brown
Finish	Tin Plated
Dimensions and Weight	
Size	L=2.74 - OD=1.09 - ID=.716 - Pin Dia=.570
Descriptions	
Description	350 PIN TERMINAL
extra long description	NSI PTS350 Aluminum Pin Terminal Al
Features	Solid Pin Terminal for Copper and Aluminum Conductors 350 MCM All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Long Description	Solid Pin Terminal for Copper and Aluminum Conductors 350 MCM All-aluminum Pin Terminals is designed for termination of both aluminum and copper conductors. The solid pin is made of aluminum and is tin-plated and pre-filled with oxide inhibitor. A cover is provided for quick installation. Rated 600 Volts.
Product Type	Aluminum Din Torminal Al Din 250 MCM
Special Features	350 MCM (STR) - 250 Pin Size
	· · · · · · · · · · · · · · · · · · ·



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	Inform	

Brand	NSi	
GTIN	00662381033604	
Manufacturers Part Number	PTS350	
UPC	662381033604	

Taxonomies, Classifications, and Categories

Category Description	TERMINALS
Туре	Solid Pin

Packaging

···-g···g		
Carton	1	
Weight Per each	0.16	

Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486
Temperature Rating	90 C