



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



RE52 1-1/2X3/4 Reducing Bushing

Crouse-Hinds

| | |
|------------------|--|
| Catalog Number | RE52 |
| Manufacturer | Crouse-Hinds |
| Description | Reducing Bushing, 1-1/2 to 3/4 In Trade Size, Re Model, Electro Galvanized and Aluminum Acrylic Paint, 1.9 In Length, 0.55 LB/Ea |
| Weight per unit | 0.5500 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |

Features

| | |
|------------|-----------------------------------|
| connection | Threaded |
| dimensions | 1.9000 IN X 1.0600 IN X 1.9000 IN |
| Material | Steel |

Material, Color, and Finish

| | |
|--------|---|
| Finish | Electrogalvanized With Chromate Treatment |
|--------|---|

Dimensions and Weight

| | |
|------|-----------------|
| Size | 1-1/2 To 3/4 In |
|------|-----------------|

Descriptions

| | |
|------------------------|--|
| Description | 1-1/2X3/4 REDUCING BUSHING |
| extra long description | CRS-H RE52 1 1/2 TO 3/4 REDUCING BU |
| Features | Crouse-Hinds series RE, REA and REC explosionproof reducers are used in rigid/IMC conduit systems to reduce conduit hubs to a smaller size (RE), connect two different sizes of conduit together (REC), or enlarge drilled and tapped openings by one NPT size (REA). PLG explosionproof plugs are used for closing threaded conduit hubs. |

Manufacturer Information

| | |
|-------|----------------|
| Brand | Eaton |
| GTIN | 00782274590202 |
| UPC | 782274590202 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | Locknuts, Bushings, Re-Bushings, Re-Washers, Threaded Plugs, Knockout Plugs |
| Type | REDUCER |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.55 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Enclosure

Class I Div 1 2 Group A B C D, Class II Div 1 Group E F G, Class II
Div 2 Group F G, Class III

standard

UL 886, CSA C22.2