



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



S803UK50 MCB S800 3P K 50a

Industrial Connections &

| | |
|------------------|--|
| Catalog Number | S803UK50 |
| Manufacturer | Industrial Connections & |
| Description | High Performance Miniature Circuit Breaker With Cage Terminal, Rated Current 50 Amps, 3 Pole, Trip Curve K, Voltage Up to 240 Vac, Ultimate Short-Circuit Breaking Capacity 50 Ka, IEC/En 60947-2, Ul 489, Csa 22.2 No. 5-02 |
| Weight per unit | 1,700.0 (lbs/each) |
| Product Category | 3 Pole Din Rail Mount Circuit |

Features

| | |
|------------------|---|
| amperage rating | 50 W |
| interrupt rating | 50 kA |
| Poles | 3 kW |
| Trip Type | OUTSIDE CORNER FITTING, OUTSIDE CORNER FITTING TYPE; ABS PLASTIC MATERIAL; 1.5 INCH L X 0.91 INCH W X 0.6 INCH H SIZE; WHITE FINISH; PAN-WAY LD10 SERIES NON-METALLIC SURFACE RACEWAY USED ON; UL, CE APPROVAL; 10 STANDARD PACKAGE; PAN-WAY[R] BRAND |
| Voltage Rating | 240 W |

Dimensions and Weight

| | |
|--------|------------------|
| Height | 95 Millimeters |
| Length | 88.5 Millimeters |
| Width | 79.5 Millimeters |

Descriptions

| | |
|------------------------|--|
| Description | MCB S800 3P K 50A |
| extra long description | ABB S803U-K50 MCB S800 3P K 50A |
| Long Description | High Performance Miniature Circuit Breaker with Cage Terminal, Rated Current 50 Amps, 3 Pole, Trip Curve K, Voltage up to 240 VAC, Ultimate Short-Circuit Breaking Capacity 50 kA, IEC/EN 60947-2, UL 489, CSA 22.2 No. 5-02 |
| Product Type | MCB S800 3P K 50a |
| Special Features | UL current limiting |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | ABB |
| GTIN | 00804325372312 |
| Manufacturers Part Number | S803U-K50 |
| UPC | 804325372312 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

| | |
|----------------------|---|
| Category Description | Loadcenter Plug In Breakers and Accessories |
| Type | Miniature circuit breakers |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 1700 |

Uses, Certifications, and Standards

| | |
|-----------------------|------------------------------|
| Application | For use as branch protection |
| Frequency Rating | 50/60 Hz |
| Operating Temperature | -25 to +60 Degrees Celcius |
| standard | UL mA |