

Kellems® Wire Management Products
Straight Male Cord Connectors
Cord Connectors

HUBBELL

Features

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tightening
- Lightweight design

Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Aluminum	Yellow	783585200378	SHC1037



Listings

UL Listed
CSA Certified

Online Resources

[eCatalog](#)

Specifications

Material	Aluminum
Form Size	F3
NPT Hub Size	3/4 Inch
Cord Diameter Range Inches (mm)	.63"-.75" (15.9-19.0)

Performance

Environmental

Hazardous Locations Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC

Operating Temperatures -30°F to +225°F (-34°C to +107°C)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.



Kellems® Wire Management Products
Straight Male Cord Connectors
Cord Connectors

HUBBELL

Features

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tightening
- Lightweight design

Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Aluminum	Yellow	783585200378	SHC1037



Listings

UL Listed
CSA Certified

Online Resources

[eCatalog](#)

Specifications

Material	Aluminum
Form Size	F3
NPT Hub Size	3/4 Inch
Cord Diameter Range Inches (mm)	.63"- .75" (15.9-19.0)

Performance

Environmental

Hazardous Locations Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC

Operating Temperatures -30°F to +225°F (-34°C to +107°C)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

