

# CONNECTORS

## Service Post Connectors

### Two-Wire Type

#### SPM Series



#### SPECIFICATIONS

- UL486A/B Listed Wire Connector.
- UL467 Listed Grounding & Bonding.

#### FEATURES

- Made from high copper content hard-drawn rod; used for connecting one or two conductors.
- Lay-in feature makes them excellent for continuous
- loop grounding and bonding.
- Used to ground to bar or plate.
- Suitable for direct burial in earth or concrete.

CAT. NO.	CONDUCTOR RANGE	STUD SIZE	HEX NUT	STD. CTN. QTY.
SPM-21L	12 SOL - 8 STR	0.250 X 20 – 1	0.375 X 24	25
SPM-22L	10 SOL - 7 STR	0.250 x 20 – 1	0.437 x 20	25
SPM-23L	8 SOL - 5 STR	0.312 x 18 – 1	0.500 x 20	25
SPM-24L	6 SOL - 3 STR	0.375 x 16 – 1.125	0.562 x 18	12
SPM-25L	10 SOL - 2 STR	0.375 x 16 – 1.125	0.625 x 18	12
SPM-26L	4 SOL - 1/0 STR	0.500 x 13 – 1.250	0.750 x 16	12
SPM-27L	2 SOL - 2 STR	0.500 x 13 – 1.250	0.875 x 14	6
SPM-29L	1 SOL - 4/0 STR	0.625 x 11 – 1.500	1.125 x 11	3

# CONNECTORS

## Service Post Connectors

### Two-Wire Type

#### SPM Series



#### SPECIFICATIONS

- UL486A/B Listed Wire Connector.
- UL467 Listed Grounding & Bonding.

#### FEATURES

- Made from high copper content hard-drawn rod; used for connecting one or two conductors.
- Lay-in feature makes them excellent for continuous
- loop grounding and bonding.
- Used to ground to bar or plate.
- Suitable for direct burial in earth or concrete.

CAT. NO.	CONDUCTOR RANGE	STUD SIZE	HEX NUT	STD. CTN. QTY.
SPM-21L	12 SOL - 8 STR	0.250 X 20 – 1	0.375 X 24	25
SPM-22L	10 SOL - 7 STR	0.250 x 20 – 1	0.437 x 20	25
SPM-23L	8 SOL - 5 STR	0.312 x 18 – 1	0.500 x 20	25
SPM-24L	6 SOL - 3 STR	0.375 x 16 – 1.125	0.562 x 18	12
SPM-25L	10 SOL - 2 STR	0.375 x 16 – 1.125	0.625 x 18	12
SPM-26L	4 SOL - 1/0 STR	0.500 x 13 – 1.250	0.750 x 16	12
SPM-27L	2 SOL - 2 STR	0.500 x 13 – 1.250	0.875 x 14	6
SPM-29L	1 SOL - 4/0 STR	0.625 x 11 – 1.500	1.125 x 11	3