

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



SS701 Wallplate, 2-G, 2.48", SS *Hubbell Wiring Devices*

Catalog Number	SS701	
Manufacturer	Hubbell Wiring Devices	
Description	Wallplates and Boxes, Metallic Plates, 2- Gang, 1) 2.48" Opening, Standard Size, Stainless Steel.	
Weight per unit	0.0150 (lbs/each)	
Product Category	Wall Plates & Covers	
Features		
cutout	1) 2.48" Opening	
gang	2 Cana	
orientation	Vertical Mount	
pallet quantity	8000	
Dimensions and Weight		
Size	2-Gang	
Thickness	0.035	
Descriptions		
Construction	Stamped	
Description	WALLPLATE, 2-G, 2.48", SS	
extra long description		
Features	Stainless steel wallplates provide solutions for a variety of industrial and commercial applications. 302/304 Type Stainless Steel Non-magnetic: 18.0% Chromium, 8% Nickel - Ideal for highly corrosive environments such as hospitals, food processing, static free requirements and more; ideal for environments subjected to heavy abuse. 430 Type Stainless Steel Magnetic: 17.0% Chromium, less than 0.5% Nickel - Aesthetically identical to the 302/304 type stainless steel wallplates and are best suited for environm	
Long Description	Wallplates and Boxes, Metallic Plates, 2- Gang, 1) 2.48" Opening, Standard Size, Stainless Steel.	
Product Type	Wallplate, 2-G, 2.48", SS	
Special Features	Protective film helps to prevent scratches and damageProvides a plush appearance with the durability of metalBrass and	

Aluminum are lacquer coated to inhibit oxidation



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer	Information
Rrand	

Brand	WIRING DEVICE-KELLEMS
GTIN	00883778201110
Manufacturers Part Number	SS701
UPC	883778201110

Taxonomies, Classifications, and Categories

Category Description	Residential plates
Туре	Plates

Packaging

,,,agg		
Carton	1	
Package	10	
Weight Per each	0.015	

Uses, Certifications, and Standards

Application	Protection against contact of live terminals and wiring. Provides finished look to installation.
Mounting	Screw Mounting
standard	UL Listed