



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



ST90300 3" Steel LT 90 Conn *Appleton/Oz Gedney*

Catalog Number	ST90300
Manufacturer	Appleton/Oz Gedney
Description	ST Series 90 Deg Liquidtight Connector With Plain Throat, Size: 3 In, Connection: Threaded X Compression, Material: Malleable Iron, Finish: Chromate, Epoxy Powder Coat/Zinc Electroplated, Thread Length: 1.19 In, Standard: Class I, Divisi
Weight per unit	11.0 (lbs/each)
Product Category	Liquid Tight Fittings

Features

connection	Threaded X Compression
Material	Malleable Iron

Material, Color, and Finish

Finish	Chromate, Epoxy Powder Coat/Zinc Electroplated
--------	--

Dimensions and Weight

Size	3
------	---

Descriptions

Description	3" STEEL LT 90 CONN
extra long description	APP ST-90300 3 IN 90DEG LFMC CONN
Long Description	ST Series 90 DEG Liquidtight Connector With Plain Throat, Size: 3 IN, Connection: Threaded X Compression, Material: Malleable Iron, Finish: Chromate, Epoxy Powder Coat/Zinc Electroplated, Thread Length: 1.19 IN, Standard: Class I, Divisi
Product Type	3 In 90DEG LFMC Conn
Special Features	Compact design with small turning radius;Ferrule provides maximum surface contact for better sealing and a continuous, permanent, positive metal-to-metal ground;High corrosion resistance;Polypropylene sealing ring with locknut standard;Seals out oil, water, dust, dirt and fumes;Suitable for wet locations;Unique long ferrule with more pronounced threads provides over four times UL pull-out requirements

Manufacturer Information

Brand	Appleton
GTIN	00781381680806
Manufacturers Part Number	ST-90300
UPC	781381680806



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	METALLIC FITTINGS
Type	ST Series 90 DEG Liquidtight Connector With Plain Throat

Packaging

Carton	1
Weight Per each	11

Uses, Certifications, and Standards

Application	For Liquidtight Flexible Metal Conduit
standard	Class I, Division 2;UL 514B, E14814, CSA C22.2 No. 18.3, 065178, NEMA FB-1