

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



SWB11 3/4 Expl-PRF Box Hubbell--Killark

Catalog Number	SWB11
Manufacturer	HubbellKillark
Description	SWB Series - Aluminum Feed-Thru Double-Gang Device Body For Use With XCS/XS/XT Cover Assemblies - Hub Size 3/4 Inch
Weight per unit	2.7 (lbs/each)
Product Category	Junction, Surface, & Back Boxe
Dimensions and Weight	
Size	9.38 in x 5.88 in x 3.44 in
Descriptions	
Description	3/4 EXPL-PRF BOX
extra long description	KLRK SWB-11 3/4" SWB DEVICE BODY DE
Long Description	SWB Series - Aluminum Feed-Thru Double-Gang Device Body For Use With XCS/XS/XT Cover Assemblies - Hub Size 3/4 Inch
Product Type	3/4" SWB Device Body Deep Feedthru
Special Features	Killark SWB SERIES CONTROL STATION BACK BOXES provide control solutions in hazardous location areas to supply;START/STOP Motor Functions, LED Pilot Light Indications and more for use with Killark XCS and XS Cover Assemblies. For use in Class 1 Division 1 & 2, Class 1 Zone 1 & 2 areas for indoor use and are Non-Factory Sealed requiring the need for a conduit seal fitting. UL Listed and CSA Certified. The SWB is offered in a wide variety of configurations from ½" to 1" dead end and feed through for single
Manufacturer Information	
Brand	KILLARK
GTIN	00783936630113
Manufacturers Part Number	SWB-11
series	SWB
UPC	783936630113
Taxonomies, Classifications, and (
	SWITCH BOXES
Туре	Aluminum device body
Packaging	
Carton	
Weight Per each	2.7



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings.
	Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where similar hazards exist. Use in conjunction with magnetic starters or contactors for remote control of motors.
Enclosure	Aluminum enclosure
environmental conditions	Hazardous locations
Mounting	WALL
standard	UL, CSA