

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TB67SA 2" Alu TB FM7 Conduit Body

Catalog Number	TB67SA
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Form 7 Conduit Outlet Body Copper-Free Aluminum, TB Shape, 2"
Weight per unit	2.1 (lbs/each)
Product Category	Alum
Features	
dimensions	9.1900 IN X 3.0000 IN X 6.1300 IN
Form	Form 7
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Height	6-1/8
Hub Size	
	9-3/16
Width	2
Descriptions	
Description	2" ALU TB FM7 CONDUIT BODY
extra long description	
Features	One hundred years after the introduction of the Condulet, Eaton remains the leader in conduit outlet bodies with its Crouse-Hinds series. The line has grown to six families manufactured in a variety of materials, and Form 7 bodies are offered in 11 different shapes to provide the most flexible offering on the market. Form 7 Condulet outlet bodies approach conduit in size for neat, compact installations. Many shapes and sizes are available for rigid threaded conduit. Our Form 7 family features an exclus
Long Description	Eaton Crouse-Hinds series Condulet Form 7 conduit outlet body, Copper-free aluminum, TB shape, 2"
Product Type	2IN NPT AI TB Form 7 CNDT Body
Manufacturer Information	
Brand	EATON CROUSE-HINDS SERIES

Mar

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274631615
Manufacturers Part Number	TB67 SA
UPC	782274631615



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cat	egories
Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Conduit outlet body
Packaging	
Carton	1
Package	2
	2.05
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Condulet

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D