



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TCF200 200A Cube Fuse *Bussmann Fuses*

Catalog Number	TCF200
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CF Fuse, TCF, Time-Delay, Dual-Element Current Limiting Cube Fuse, 200 A, Indicating Fuse, Interrupting Rating Of 100 Ka At 300 VDC and 200 Ka At 600 Vac
Weight per unit	0.4400 (lbs/each)
Product Category	Tools & Testers

### Features

amperage rating	200 A
class	Class CF
connection	Blade End
dimensions	2.9500 IN X 1.3200 IN X 3.6300 IN
Fuse Class	Class CF
interrupt rating	200 kAIC
Material	Glass Filled PES
Voltage Rating	600 V

### Descriptions

Description	200A CUBE FUSE
extra long description	EFSE TCF200 TIME DELAY CUBEFUSE 200
Features	The revolutionary Bussmann™ series Low-Peak™ CUBEFuse™ delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 200 A, indicating fuse, interrupting rating of 100 kA at 300 Vdc and 200 kA at 600 Vac
Product Type	Time Delay Cubefuse 200A Ind
Special Features	Finger Safe

### Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712697804
Manufacturers Part Number	TCF200
UPC	051712697804



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description Fuses & Fuse Accessories

Type FUSE

## Packaging

Carton 1

Weight Per each 0.44

## Uses, Certifications, and Standards

Application OtherDatacenters - Facilities: Power DistributionCommercial /  
Institutional Buildings / Structures - Critical PowerInd Facilities &  
Factories - Facility: Power Distribution and ControlStationary  
Machinery and Equipment Outside Factory - HVAC

standard UL Listed,RoHS Compliant