Eaton TCF60RN

Catalog Number: TCF60RN

Eaton Bussmann Series Class CF fuse, TCF, time-delay, dualelement current limiting cube fuse, 60 A, non-idicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac

General specifications

Eaton Bussmann series TCF fuse



Product Name Catalog Number TCF60RN

UPC Product Length/Depth

051712222556 2.13 in

Product Height Product Width

1.9 in 1 in

Product Weight Warranty

0.17 lb Not Applicable

Compliances Certifications CE Marked **UL Listed RoHS Compliant CSA** Certified



Electrical rating

Amperage Rating

60 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

100 kAIC at 300 Vdc 300 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Color

Black

Fuse type

Class CF

Time delay

Material

Glass filled PES

Number of elements

Dual

Packaging type

Standard

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Mounting method

Chassis

35 mm DIN rail

Special features

Finger safe

Used with

TCFH60N, CCP2-3-60CF

Resources

Catalogs

Bussmann Full Line Catalog

Low Voltage Branch Circuit Fuse Chapter

Compliance information

RoHS Search Tool

Multimedia

The Power of Space

Bussmann series Fuseology

Technical data sheets

Bussmann series UL Class CF CUBEFuse data sheet no. 9000



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia

Eaton TCF60RN

Catalog Number: TCF60RN

Eaton Bussmann Series Class CF fuse, TCF, time-delay, dualelement current limiting cube fuse, 60 A, non-idicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac

General specifications

Eaton Bussmann series TCF fuse



Product Name Catalog Number TCF60RN

UPC Product Length/Depth

051712222556 2.13 in

Product Height Product Width

1.9 in 1 in

Product Weight Warranty

0.17 lb Not Applicable

Compliances Certifications CE Marked **UL Listed RoHS Compliant CSA** Certified



Electrical rating

Amperage Rating

60 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

100 kAIC at 300 Vdc 300 kAIC at 600 Vac

Response time

10 sec at 500%

Voltage rating

600 Vac, 300 Vdc

Physical details

Color

Black

Fuse type

Class CF

Time delay

Material

Glass filled PES

Number of elements

Dual

Packaging type

Standard

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Mounting method

Chassis

35 mm DIN rail

Special features

Finger safe

Used with

TCFH60N, CCP2-3-60CF

Resources

Catalogs

Bussmann Full Line Catalog

Low Voltage Branch Circuit Fuse Chapter

Compliance information

RoHS Search Tool

Multimedia

The Power of Space

Bussmann series Fuseology

Technical data sheets

Bussmann series UL Class CF CUBEFuse data sheet no. 9000



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2025 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia