



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TCF60RN Buss TCF60RN Cubefuse, TCF 60A Non-Bussmann Fuses

Catalog Number	TCF60RN
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series Class CF Fuse, TCF, Time-Delay, Dual-Element Current Limiting Cube Fuse, 60 A, Non-Indicating Fuse, Interrupting Rating Of 100 Ka At 300 VDC and 300 Ka At 600 Vac
Weight per unit	2.1 (lbs/each)
Product Category	Tools & Testers

### Features

amperage rating	60 A
class	Class CF
connection	Blade End
dimensions	2.1300 IN X 1.0000 IN X 1.9000 IN
element	Dual
interrupt rating	100 kAIC at 300 Vdc300 kAIC at 600 Vac
Material	Glass Filled PES
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

### Descriptions

Description	BUSS TCF60RN CUBEFUSE, TCF 60A NON-
extra long description	EFSE TCF60RN CUBEFUSE, TCF 60A NON-
Features	The revolutionary Bussmann™ series Low-Peak™ CUBEFuse™ delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann Series Class CF fuse, TCF, time-delay, dual-element current limiting cube fuse, 60 A, non-indicating fuse, interrupting rating of 100 kA at 300 Vdc and 300 kA at 600 Vac
Product Type	Cubefuse, TCF 60A Non-Ind
Special Features	Finger Safe

### Manufacturer Information

Brand	Bussmann Fuses
Manufacturers Part Number	TCF60RN



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Type FUUSE

## Packaging

Carton 1

Weight Per each 2.09

## Uses, Certifications, and Standards

Application Ind Facilities & Factories - Facility: Safety and Security  
SystemsDatacenters - Facilities: Power DistributionCommercial /  
Institutional Buildings / Structures - Critical PowerInd Facilities &  
Factories - Facility: Power Distribution and ControlStationary  
Machinery and Equipment Outside Factory - HVAC

Mounting 35 mm DIN Rail, Chassis

standard CSA Certified ,UL Listed,CE Marked,RoHS Compliant