

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



THHN12STBRMINICP THHN 12 STR Brown 1000' Mini CP

| Catalog Number | THHN12STBRMINICP |
|--|--|
| Manufacturer | Southwire Company |
| Description | 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant Ii. Rated Both THHN and THWN. Also Rated MTW and Awm. Simpull Technology For Easier Pulling. |
| Weight per unit | |
| Product Category | THHN-T90-STR (Stranded) |
| Features | |
| Conductor Size | 12 |
| media | Yes |
| Number of Conductors | 1 |
| Voltage Rating | 600 |
| Material, Color, and Finish Insulation Material | PVC |
| Jacket Material | Nylon |
| Dimensions and Weight Length | 1000 |
| Descriptions | |
| Description | THHN 12 STR BROWN 1000' MINI CP |
| extra long description | SWC 50010504 TUUN 12 Str Cu Dn 1000 |
| Features | SIMpull THHN copper conductors are primarily used in conduit and cable trays for services, feeders and branch circuits in commercial or industrial applications as specified in the National Electrical Code. Voltage for all applications is 600 volts. SIMpull THHN copper conductors are designed to be installed without application of a pulling lubricant. |
| Long Description | 600 Volts. Copper Conductor. Thermoplastic Insulation/Nylon Sheath, Heat, Moisture, Gasoline and Oil Resistant II. Rated both THHN and THWN. Also rated MTW and AWM. SIMpull Technology for easier pulling. |
| Product Type | |
| Special Features | Nolubo |
| Manufacturer Information Brand | Copper |
| GTIN | 00032886940545 |
| Manufacturers Part Number | 58018504 |
| UPC | 032886940545 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Taxonomies, Classifications, and Categories | | |
|---|------------|--|
| Туре | THHN | |
| Availability | | |
| minimum qty | 1000 | |
| Packaging Carton | 1 | |
| Weight Per foot | 0.024 | |
| Uses, Certifications, and Standards Application | Commerical | |