

# Eaton TRL04

Catalog Number: TRL04

Eaton 4-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

## General specifications



### Product Name

Eaton TR timing relay

### Catalog Number

TRL04

### UPC

786685313573

### Product Length/Depth

1.3 in

### Product Height

3.43 in

### Product Width

1.8 in

### Product Weight

0.09 lb

### Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Compliances

CE Marked  
TUV

### Certifications

CSA Certified  
cULus Listed

## Product specifications

### Frequency rating

50-60 Hz

### Enclosure

IP40

### Enclosure material

Self-extinguishing plastic

### Contact configuration

SPDT

### Time delay

0.05 seconds-100 hours

### Series

TR

### Functions

ON/OFF delay

Power triggered

Single shot leading edge voltage controlled

Flasher-pause first

### Input voltage

24-240 Vac/dc

### Mounting method

Compact DIN rail

## Resources

### Installation instructions

[TRL04 and TRL07 Installation Instructions](#)

### Specifications and datasheets

[Eaton Specification Sheet - TRL04](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)

# Eaton TRL04

Catalog Number: TRL04

Eaton 4-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure

## General specifications



### Product Name

Eaton TR timing relay

### Catalog Number

TRL04

### UPC

786685313573

### Product Length/Depth

1.3 in

### Product Height

3.43 in

### Product Width

1.8 in

### Product Weight

0.09 lb

### Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Compliances

CE Marked  
TUV

### Certifications

CSA Certified  
cULus Listed

## Product specifications

### Frequency rating

50-60 Hz

### Enclosure

IP40

### Enclosure material

Self-extinguishing plastic

### Contact configuration

SPDT

### Time delay

0.05 seconds-100 hours

### Series

TR

### Functions

ON/OFF delay

Power triggered

Single shot leading edge voltage controlled

Flasher-pause first

### Input voltage

24-240 Vac/dc

### Mounting method

Compact DIN rail

## Resources

### Installation instructions

[TRL04 and TRL07 Installation Instructions](#)

### Specifications and datasheets

[Eaton Specification Sheet - TRL04](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)