

Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



General specifications

Product Name
Eaton TR timing relay

UPC
786685313580

Product Height
3.43 in

Product Weight
0.16 lb

Compliances
TUV
CE Marked

Catalog Number
TRL07

Product Length/Depth
2.56 in

Product Width
0.69 in

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
cULus Listed
CSA Certified

Product specifications

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

SPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

Input voltage

24-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Installation instructions

[TRL04 and TRL07 Installation Instructions](#)

Specifications and datasheets

[Eaton Specification Sheet - TRL07](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)

Eaton TRL07

Catalog Number: TRL07

Eaton 7-function Universal TR Series Timing Relay, style terminals, 0.05 seconds-100 hours time delay, 24-240 Vac/dc input voltage, Compact DIN rail mount, SPDT contact configuration, IP40 enclosure



General specifications

Product Name
Eaton TR timing relay

Catalog Number
TRL07

UPC
786685313580

Product Length/Depth
2.56 in

Product Height
3.43 in

Product Width
0.69 in

Product Weight
0.16 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
TUV
CE Marked

Certifications
cULus Listed
CSA Certified

Product specifications

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

SPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

Single shot leading or trailing edge voltage controlled and control input

ON delay control signal start

ON/OFF delay

Trailing edge OFF

Power triggered

Flasher-pause first

Input voltage

24-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Installation instructions

[TRL04 and TRL07 Installation Instructions](#)

Specifications and datasheets

[Eaton Specification Sheet - TRL07](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)