

Eaton TRL27

Catalog Number: TRL27

Eaton 7-function universal TR series timing relay, style terminals, 0.05 seconds-100 hours time delay, 12-240 Vac/dc input voltage, Compact DIN rail mount, DPDT contact configuration, IP40 enclosure



Photo is representative

General specifications

Product Name
Eaton TR timing relay

UPC
786685313597

Product Height
3.43 in

Product Weight
0.24 lb

Compliances
CE Marked
TUV

Catalog Number
TRL27

Product Length/Depth
2.56 in

Product Width
1.38 in

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Certifications
CSA Certified
cULus Listed

Product specifications

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

DPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

ON/OFF delay

Single shot leading or trailing edge voltage controlled and control input

Power triggered

Trailing edge OFF

ON delay control signal start

Flasher-pause first

Input voltage

12-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Specifications and datasheets

[Eaton Specification Sheet - TRL27](#)

Eaton TRL27

Catalog Number: TRL27

Eaton 7-function universal TR series timing relay, style terminals, 0.05 seconds-100 hours time delay, 12-240 Vac/dc input voltage, Compact DIN rail mount, DPDT contact configuration, IP40 enclosure



Photo is representative

General specifications

Product Name
Eaton TR timing relay

Catalog Number
TRL27

UPC
786685313597

Product Length/Depth
2.56 in

Product Height
3.43 in

Product Width
1.38 in

Product Weight
0.24 lb

Warranty
Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Compliances
CE Marked
TUV

Certifications
CSA Certified
cULus Listed

Product specifications

Frequency rating

50-60 Hz

Enclosure

IP40

Enclosure material

Self-extinguishing plastic

Contact configuration

DPDT

Time delay

0.05 seconds-100 hours

Series

TR

Functions

ON/OFF delay

Single shot leading or trailing edge voltage controlled and control input

Power triggered

Trailing edge OFF

ON delay control signal start

Flasher-pause first

Input voltage

12-240 Vac/dc

Mounting method

Compact DIN rail

Resources

Specifications and datasheets

[Eaton Specification Sheet - TRL27](#)