

Type

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

TY524MX 5.50" Uv Rated "Ty-Rap" Cable Tie Abb Installation Products, Inc

Catalog Number	TY524MX		
Manufacturer	Abb Installation Products, Inc		
Description	Cable Tie, Black Polyamide (Nylon 6.6) For Temperatures Up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant For Indoor and Outdoor Applications, Length Of 137MM (5.4 Inches), Width Of 3.6MM (0.14 Inches), Thickness Of 1MM (0.04 Inch), Tensile Strength Rating Of 178 Newtons (40 Pounds)		
Weight per unit	0.0029 (lbs/each)		
Product Category	Cable Ties & Wraps		
Features			
Tensile Strength	40		
Dimensions and Weight			
Length	5.4		
Thickness	0.04		
Width	0.14		
Descriptions			
Description	5.50" UV RATED "TY-RAP" CABLE TIE		
extra long description	ABB TY524MX CBL TIE 30LB 5.5 UV BLA		
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 85 Degrees Celsius (185 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 137mm (5.4 Inches), Width of 3.6mm (0.14 Inches), Thickness of 1mm (0.04 Inch), Tensile Strength Rating of 178 Newtons (40 Pounds)		
Product Type	CBL Tie 30LB 5.5 Uv Black 2-PC Dis		
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time		
Manufacturer Information			
Brand	Ty-Rap		
GTIN	00786210806990		
Manufacturers Part Number	TY524MX		
UPC	786210806990		
Taxonomies, Classifications, and	Categories		
Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps		

HIGH PERFORMANCE



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	100	
Package	1000	
Weight Per each	0.0029	