



MILBANK
ENERGY AT WORK

U3862



| | | | |
|-------------------------------|---|--------------------|-----------------------|
| Catalog Number | U3862 | Enclosure | Painted Steel |
| Marketing Product Description | 60 Ampere Fused Alternating Current Disconnect Pull Out | Mounting | Surface Mount |
| UPC | 784572586932 | Size | 3.107L x 5.2W x 9.25H |
| Length (IN) | 3.107 | Conduit Connection | Knockouts |
| Width (IN) | 5.2 | | |
| Height (IN) | 9.25 | | |
| Weight (LB) | 4 | | |
| Brand Name | Milbank | | |
| Type | Air Conditioner Disconnect | | |
| Special Features | 10 Horse Power | | |
| Application | Metering Accessory | | |
| Standard | UL Listed;Type 3R | | |
| Voltage Rating | Up to 240 Volts Alternating Current | | |
| Amperage Rating | 60 Ampere | | |
| Interrupt Rating | 10,000 Ampere Interrupting Capacity | | |
| Number Of Poles | 2 | | |
| Trip Type | Thermal Overload and Short Circuit Current | | |
| Contact Configuration | Pull Out | | |
| Contact Rating | 60 Ampere Up to 240 Volts Alternating Current | | |
| Connection | Pullout | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.



MILBANK
ENERGY AT WORK

U3862



| | | | |
|-------------------------------|---|--------------------|-----------------------|
| Catalog Number | U3862 | Enclosure | Painted Steel |
| Marketing Product Description | 60 Ampere Fused Alternating Current Disconnect Pull Out | Mounting | Surface Mount |
| UPC | 784572586932 | Size | 3.107L x 5.2W x 9.25H |
| Length (IN) | 3.107 | Conduit Connection | Knockouts |
| Width (IN) | 5.2 | | |
| Height (IN) | 9.25 | | |
| Weight (LB) | 4 | | |
| Brand Name | Milbank | | |
| Type | Air Conditioner Disconnect | | |
| Special Features | 10 Horse Power | | |
| Application | Metering Accessory | | |
| Standard | UL Listed;Type 3R | | |
| Voltage Rating | Up to 240 Volts Alternating Current | | |
| Amperage Rating | 60 Ampere | | |
| Interrupt Rating | 10,000 Ampere Interrupting Capacity | | |
| Number Of Poles | 2 | | |
| Trip Type | Thermal Overload and Short Circuit Current | | |
| Contact Configuration | Pull Out | | |
| Contact Rating | 60 Ampere Up to 240 Volts Alternating Current | | |
| Connection | Pullout | | |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.