

Type UA

UL Listed, CSA Certified
Liquid-Tight Flexible Metal Conduit (LFMC)



Construction

- Constructed of continuously interlocked hot dipped zinc galvanized steel core for exceptional crush and corrosion resistance.
- Durable, sunlight resistant and flame retardant thermoplastic PVC jacket that resists heat, oil and chemical breakdown.

Installation

- Conduit used with standard liquid-tight connector for easy installation. IP 66/67 Rated when installed with approved connectors.
- Approved for both exposed and concealed locations. Rated for temperature ranges -4°F to + 140°F (-20°C to +60°C).
- Approved as an equipment grounding conductor in sizes 3/8" through 1-1/4" if the total grounding path is 6 ft. or less and the circuit conductors are protected by over 20 amps for 3/8" and 1/2" and 60 amps or less for 3/4" through 1-1/4".
- Suitable for use in hazardous locations per NEC Articles 501 Class I Div. 2, Article 502 Class II Div. 1 & 2, Article 503 Class III Div. 1 & 2.
- Manufactured in a full range of trade sizes from 3/8" through 4".
- Approved for direct burial and in concrete trade sizes 3/8" through 4".
- Complies with UL Standard 360 File No. E18917; CSA C22.2 File No. 158897; and NEC Article 350.



Square-Locked Design with integral bonding wire 3/8" through 1-1/4"



Interlocked Design 1-1/2" through 4" with no bonding wire

NEC Articles

- Article 250.118 (6) Equipment Grounding
- Article 300.22 (D) Information Technology Equipment
- Article 350 Liquid-Tight Flexible Metal Conduit (LFMC)
- Article 501.10 (B) (2) Class I Div. 2
- Article 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
- Article 503.10 (A) (3) and (B) Class III Div. 1 & 2
- Article 620.21 Elevator Wiring Methods
- Article 645.5 (E) (2) Under Raised Floors


www.ul.com www.csa-international.org
www.nfpa.org www.naed.org
www.nema.org www.anametelectrical.com

U.L. LISTED • CSA CERTIFIED • RoHS WEEE COMPLIANT



Type UA

Gray or Black thermoplastic PVC jacket with integral bonding wire 3/8" through 1-1/4"



Product Specifications

Ordering Information

| Electrical Trade Size | Inside Diameter | | Outside Diameter | | Approx Inside Bend Radius | Approx Weight lbs. | Small Carton | | Standard Carton | | Small Reels | | Standard Reels | | | |
|-----------------------|-----------------|----|------------------|--------|---------------------------|--------------------|--------------|-------------|-----------------|-------|-------------|-------|----------------|-------|--------|-------|
| | Inches | mm | Inches | | | | Inches | PER 100 FT. | Length | NAED | Length | NAED | Length | NAED | Length | NAED |
| | | | MIN. | MAX. | | | Feet | PIN | Feet | PIN | Feet | PIN | Feet | PIN | | |
| 3/8 | 12 | | .484 | -.504 | .690 | -.710 | 3.0 | 25 | 100 | 34202 | 200 | 34201 | 800 | 34204 | 1500 | 34203 |
| 1/2 | 16 | | .622 | -.642 | .822 | -.840 | 3.5 | 29 | 100 | 34212 | 200 | 34211 | 500 | 34214 | 1000 | 34213 |
| 3/4 | 21 | | .820 | -.840 | 1.030 | -1.050 | 5.0 | 44 | 100 | 34222 | 150 | 34221 | 500 | 34228 | 1000 | 34229 |
| 1 | 27 | | 1.041 | -1.066 | 1.290 | -1.315 | 6.0 | 73 | | 100 | 34231 | 400 | 34238 | | | |
| 1-1/4 | 35 | | 1.380 | -1.410 | 1.630 | -1.660 | 7.0 | 100 | | 50 | 34241 | 250 | 34248 | | | |
| 1-1/2 | 41 | | 1.575 | -1.600 | 1.865 | -1.900 | 5.5 | 112 | | 50 | 34251 | 150 | 34254 | | | |
| 2 | 53 | | 2.020 | -2.045 | 2.340 | -2.375 | 7.0 | 148 | | 50 | 34261 | 100 | 34268 | | | |
| 2-1/2 | 63 | | 2.480 | -2.505 | 2.840 | -2.875 | 9.5 | 182 | | 25 | 34272 | | | 100 | 34274 | |
| 3 | 78 | | 3.070 | -3.100 | 3.460 | -3.500 | 15 | 255 | | 25 | 34281 | | | 100 | 34284 | |
| 3-1/2 | 91 | | 3.500 | -3.540 | 3.960 | -4.000 | 16 | 314 | | 25 | 34301 | | | 100 | 34304 | |
| 4 | 103 | | 4.000 | -4.040 | 4.460 | -4.500 | 17 | 362 | | 25 | 34291 | | | 100 | 34294 | |

Note: 1. Gray - Specification above.
2. Black - Change third number in NAED code to "0".
3. Other Colors are available upon request.

TYPICAL SPECIFICATION:

Conduit shall be Anaconda SEALTITE® Type UA. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked hot dipped zinc galvanized steel core with an integral bonding wire in sizes 3/8" thru 1-1/4". Conduit shall have a sunlight resistant and flame retardant PVC jacket in electrical trade sizes 3/8" thru 4". Conduit shall be UL listed, CSA certified and IP 66/67 rated when installed with approved end connectors.

Type UA

UL Listed, CSA Certified
Liquid-Tight Flexible Metal Conduit (LFMC)



Construction

- Constructed of continuously interlocked hot dipped zinc galvanized steel core for exceptional crush and corrosion resistance.
- Durable, sunlight resistant and flame retardant thermoplastic PVC jacket that resists heat, oil and chemical breakdown.

Installation

- Conduit used with standard liquid-tight connector for easy installation. IP 66/67 Rated when installed with approved connectors.
- Approved for both exposed and concealed locations. Rated for temperature ranges -4°F to + 140°F (-20°C to +60°C).
- Approved as an equipment grounding conductor in sizes 3/8" through 1-1/4" if the total grounding path is 6 ft. or less and the circuit conductors are protected by over 20 amps for 3/8" and 1/2" and 60 amps or less for 3/4" through 1-1/4".
- Suitable for use in hazardous locations per NEC Articles 501 Class I Div. 2, Article 502 Class II Div. 1 & 2, Article 503 Class III Div. 1 & 2.
- Manufactured in a full range of trade sizes from 3/8" through 4".
- Approved for direct burial and in concrete trade sizes 3/8" through 4".
- Complies with UL Standard 360 File No. E18917; CSA C22.2 File No. 158897; and NEC Article 350.



Square-Locked Design with integral bonding wire 3/8" through 1-1/4"



Interlocked Design 1-1/2" through 4" with no bonding wire

NEC Articles

- Article 250.118 (6) Equipment Grounding
- Article 300.22 (D) Information Technology Equipment
- Article 350 Liquid-Tight Flexible Metal Conduit (LFMC)
- Article 501.10 (B) (2) Class I Div. 2
- Article 502.10 (A) (2) and (B) (2) Class II Div. 1 & 2
- Article 503.10 (A) (3) and (B) Class III Div. 1 & 2
- Article 620.21 Elevator Wiring Methods
- Article 645.5 (E) (2) Under Raised Floors


www.ul.com www.csa-international.org
www.nfpa.org www.naed.org
www.nema.org www.anametelectrical.com

U.L. LISTED • CSA CERTIFIED • RoHS WEEE COMPLIANT



Type UA

Gray or Black thermoplastic PVC jacket with integral bonding wire 3/8" through 1-1/4"



Product Specifications

Ordering Information

| Electrical Trade Size | Inside Diameter | | Outside Diameter | | Approx Inside Bend Radius | Approx Weight lbs. | Small Carton | | Standard Carton | | Small Reels | | Standard Reels | | | |
|-----------------------|-----------------|----|------------------|--------|---------------------------|--------------------|--------------|-------------|-----------------|-------|-------------|-------|----------------|-------|--------|-------|
| | Inches | mm | Inches | | | | Inches | PER 100 FT. | Length | NAED | Length | NAED | Length | NAED | Length | NAED |
| | | | MIN. | MAX. | | | Feet | PIN | Feet | PIN | Feet | PIN | Feet | PIN | | |
| 3/8 | 12 | | .484 | -.504 | .690 | -.710 | 3.0 | 25 | 100 | 34202 | 200 | 34201 | 800 | 34204 | 1500 | 34203 |
| 1/2 | 16 | | .622 | -.642 | .822 | -.840 | 3.5 | 29 | 100 | 34212 | 200 | 34211 | 500 | 34214 | 1000 | 34213 |
| 3/4 | 21 | | .820 | -.840 | 1.030 | -1.050 | 5.0 | 44 | 100 | 34222 | 150 | 34221 | 500 | 34228 | 1000 | 34229 |
| 1 | 27 | | 1.041 | -1.066 | 1.290 | -1.315 | 6.0 | 73 | | 100 | 34231 | 400 | 34238 | | | |
| 1-1/4 | 35 | | 1.380 | -1.410 | 1.630 | -1.660 | 7.0 | 100 | | 50 | 34241 | 250 | 34248 | | | |
| 1-1/2 | 41 | | 1.575 | -1.600 | 1.865 | -1.900 | 5.5 | 112 | | 50 | 34251 | 150 | 34254 | | | |
| 2 | 53 | | 2.020 | -2.045 | 2.340 | -2.375 | 7.0 | 148 | | 50 | 34261 | 100 | 34268 | | | |
| 2-1/2 | 63 | | 2.480 | -2.505 | 2.840 | -2.875 | 9.5 | 182 | | 25 | 34272 | | | 100 | 34274 | |
| 3 | 78 | | 3.070 | -3.100 | 3.460 | -3.500 | 15 | 255 | | 25 | 34281 | | | 100 | 34284 | |
| 3-1/2 | 91 | | 3.500 | -3.540 | 3.960 | -4.000 | 16 | 314 | | 25 | 34301 | | | 100 | 34304 | |
| 4 | 103 | | 4.000 | -4.040 | 4.460 | -4.500 | 17 | 362 | | 25 | 34291 | | | 100 | 34294 | |

Note: 1. Gray - Specification above.
2. Black - Change third number in NAED code to "0".
3. Other Colors are available upon request.

TYPICAL SPECIFICATION:

Conduit shall be Anaconda SEALTITE® Type UA. Conduit shall provide a flexible liquid-tight raceway for wiring and shall be constructed of continuously interlocked hot dipped zinc galvanized steel core with an integral bonding wire in sizes 3/8" thru 1-1/4". Conduit shall have a sunlight resistant and flame retardant PVC jacket in electrical trade sizes 3/8" thru 4". Conduit shall be UL listed, CSA certified and IP 66/67 rated when installed with approved end connectors.