

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

UAG34500 3/4" Ua Sealtite Conduit, Bonded UI 500' *Southwire Company*

Catalog Number	UAG34500	
Manufacturer	Southwire Company	
Description	TITAN2 Type UI LFMC Is Manufactured With A Spiral Wound St Of Heavy Gauge Corrosion-Resistant Hot-Dipped Galvanized Steel. For 3/8" Through 1-1/4" Trade Sizes The Core Is Constructed With A Square Locked Steel Strip With An Integral	
	Copperbonding Strip Enclosed Within The Steel Convolutions. For 1-1/2" Through 4" Trade Sizes The Core Is Constructed With A Fully Interlocked Steel Strip. A Rugged Flame Retardant Flexible PVC Jacket Is Extruded Over The Steel Core. The Grey Jacket Resists Oils Mild	
Weight per unit	0.3800 (lbs/each)	
Product Category	Conduit & Raceways	
eatures	•	
outside diameter	1040	
imensions and Weight		
Length	500	
escriptions		
Description	3/4" UA SEALTITE CONDUIT, BONDED UL 500'	
extra long description	SWC 55082705 Titan2 Type UL Liquidt	
Long Description	Titan2 Type UL LFMC is manufactured with a spiral wound strip of heavy gauge corrosion-resistant hot-dipped galvanized stee For 3/8" through 1-1/4" trade sizes the core is constructed with	
	a square locked steel strip with an integral copperbonding strip enclosed within the steel convolutions. For 1-1/2" through 4"	
	trade sizes the core is constructed with a fully interlocked steel	
	strip. A rugged flame retardant flexible PVC jacket is extruded	
Product Type	over the steel core. The grey jacket resists oils mild TITAN2 Type UI Liquidtight Flexible Metal Conduit	
3 r	THANZ Type of Eigenetight Flexible Wetar conduit	
lanufacturer Information Brand	Flexible Conduit	
GTIN	00032886052637	
Manufacturers Part Number	55082705	
UPC	032886052637	

Liquid Tight

Category Description



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size		
Trade Size	3/4	
Packaging		
Carton	500	
Weight Per each	0.38	