Eaton UATH5330UFLCH

Catalog Number: UATH5330UFLCH

Eaton meter socket, 1-pos commercial or resi service, 320A, Over/under, 5x5 inch hub open, 3/8 inch stud, 5-jaw, 1-ph, 3/8 inch stud, Lever bypass, Gnd conn (#14-#2 Cu), Al, Triplex, 3-wire, Ringless, 600 Vac

General specifications



Eaton meter socket

UPC

782116168934

Product Height

39.88 in

Product Weight

38 lb

Catalog Number

UATH5330UFLCH

Product Length/Depth

6.5 in

Product Width

20 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Certifications

UL Listed



Product specifications

Type

Single-position commercial or residential service

Amperage Rating

320A

Feed type

Top/bottom

Number of jaws

Four-jaw

Phase

Single-phase

Utility approvals

FL: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

IN: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

KY: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

NC: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

OH: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

SC: MEG (Duke Energy, Florida Power, Tampa Electric, Gulf

Power, Oklahoma Gas and Electric)

FL: Tallahassee City Electric

Line

3/8 in stud

Load

3/8 in stud

Enclosure material

Aluminum

Number of wires

Three-wire

Hub type

5 x 5 hub opening

Connection

Ground connection

Security

Resources

Specifications and datasheets

Eaton Specification Sheet - UATH5330UFLCH

Ringless

Voltage rating

600 V

Bypass

Lever

Number of sockets



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia