

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UNL205 3/4" Female/Male 90D Elbow

| Catalog Number | UNL205 |
|------------------|---|
| Manufacturer | Crouse-Hinds |
| Description | 90° Elbow, 3/4 to 3/4 In Trade Size, Unl Model, Angle Shape, |
| | Electro Galvanized and Aluminum Acrylic Paint, Female to Male |
| | Connection, 2-7/8 In Length, 1-13/16 In Width, 1-13/16 In |
| | Diameter, 0.75 LB |
| Weight per unit | 0.7500 (lbs/each) |
| Product Category | Rigid Conduit Fittings - Steel |
| itures | |
| connection | Threaded |

Features

| connection | Threaded |
|------------|-----------------------------------|
| dimensions | 2.8800 IN X 1.8100 IN X 2.0000 IN |

Descriptions

| extra long description CRS-H UNL205 3/4 NPT 90 DEGREE ANG Features Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion | cription | 4" FEMALE/MALE 90D ELBOW |
|---|--------------------|--|
| rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion | a long description | S-H UNL205 3/4 NPT 90 DEGREE ANG |
| contraction of conduit and compensate for conduit cut too: Available in a variety of materials, including stainless steel, suit customer preferences. Explosionproof elbows allow for | ures | pid/IMC conduit systems to connect conduit to conduit, a nduit fitting, junction box or device enclosure. Expansion alons are also available, which allow for expansion and ntraction of conduit and compensate for conduit cut too short. vailable in a variety of materials, including stainless steel, to it customer preferences. Explosionproof elbows allow for a 90° ange in direction to the conduit run, or when terminating at a |

Manufacturer Information

| Brand | EATON CROUSE-HINDS SERIES |
|-------|---------------------------|
| GTIN | 00782274647302 |
| UPC | 782274647302 |

Taxonomies, Classifications, and Categories

| Category Description | HAZARDOUS LOCATION FITTINGS |
|----------------------|-----------------------------|
| Type | Union |
| | |

Packaging

| 5 5 | | |
|-----------------|------|--|
| Carton | 1 | |
| Packano | 10 | |
| Weight Per each | 0.75 | |

Uses, Certifications, and Standards

| Application | Ind Facilities & Factories - Industrial Facilities/Factories - Other |
|-------------|--|
| Enclosure | Condulet |
| standard | UL 886, CSA C22.2 |