

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UNY150NRA 1-1/2" Fem/Male Union *Appleton/Oz Gedney*

Catalog Number	UNY150NRA
Manufacturer	Appleton/Oz Gedney
Description	Unilets Uny Union, Trade Size: 1-1/2 In, Outside Diameter: 3.06 In, Length: 3-1/4 In, Flexibility: Rigid and Imc, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Connection: Male Threaded X Female Threaded, Finish: Natural, Stan
Weight per unit	0.7000 (lbs/each)
Product Category	Aluminum
atures	
connection	Male Threaded X Female Threaded
outside diameter	3.06
mensions and Weight	
Length	3-1/4
	5-1/
escriptions Description	1-1/2" FEM/MALE UNION
Description extra long description	APP UNY150NR-A 1-1/2 UNION CONN TYP
Long Description	UNILETS UNY Union, Trade Size: 1-1/2 IN, Outside Diameter: 3.00 IN, Length: 3-1/4 IN, Flexibility: Rigid And IMC, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Connection: Male Threaded X Female Threaded, Finish: Natural, Stan
Product Type	1-1/2 Union Conn Type Uny
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity; Concentric ring interlocked design sizes makes possible smaller diameter, allowing use in tighter spaces; Explosionproof, dust-ignitionproof; Smooth, rounded integral bushing in each hub protects conductor insulation; UNY unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit; With removable male nipple
anufacturer Information	
Brand	Appleton
GTIN	00781381257763
Manufacturers Part Number	UNY150NR-A
UPC	781381257763

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Туре	UNY Union



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	1-1/2
Packaging Carton	5
Package	25
Weight Per each	0.7
Uses, Certifications, and Standa	rds
Application	For Connecting Conduit To Enclosure
standard	and Class II, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181
	Certified; Class II, Groups E, F, G; UL 886 (1203), UL File Number
	E10444, UL Listed for Class I, Groups B, C, d