Specifications

Photo is representative



Eaton V48M28T1516

DOE 2016 Efficient Transformer, Three-phase, PV: 480V, Taps: 2 at +2.5% FCAN, 4 at -2.5% FCBN, SV: 208Y/120V, 150°C, 15 kVA, Al windings

General specifications		
PRODUCT NAME	Eaton General purpose ventilated transformer	
CATALOG NUMBER	V48M28T1516	
UPC	786680147517	
PRODUCT LENGTH/DEPTH	17.75 in	
PRODUCT HEIGHT	28 in	
PRODUCT WIDTH	21.88 in	
PRODUCT WEIGHT	228 lb	
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
COMPLIANCES	DOE2016 Efficient	
CERTIFICATIONS	UL Listed	
CATALOG NOTES	10 CFR Part 431 (2016) Efficient	

Physical Attributes	
COIL MATERIAL	Aluminum
ENCLOSURE	NEMA 2
FRAME	939
INSULATION	220 °C
TAP SIZE	2 at +2.5% FCAN; 4 at -2.5% FCBN
WIRING CONNECTION	280B

Performance Ratings	
EFFICIENCY	10 CFR Part 431-2016 (DOE 2016)
FREQUENCY RATING	60 Hz
KVA RATING	15 kVA
PRIMARY VOLTAGE	480 V
SECONDARY VOLTAGE	208Y/120 V
SOUND LEVEL	45 dB
TEMPERATURE RISE	150 °C rise
VOLT AMPERE RATING	15 kVA

Miscellaneous Resources

WEATHERSHIELD	WS57	SPECIFICATIONS AND	Eaton Specification Sheet -
		DATASHEETS	V48M28T1516

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.







