Specifications

Photo is representative



Eaton V48M28T7516CU

Eaton General purpose ventilated transformer, Fungus proof, CU windings, DOE 2016, NEMA 2, FR942, 220°C, 75 kVA, Floor/wall mnt upright only, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 75 kVA

General specifications		
PRODUCT NAME	Eaton General purpose ventilated transformer	
CATALOG NUMBER	V48M28T7516CU	
UPC	786680192012	
PRODUCT LENGTH/DEPTH	24 in	
PRODUCT HEIGHT	43 in	
PRODUCT WIDTH	30.5 in	
PRODUCT WEIGHT	632 lb	
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
COMPLIANCES	DOE2016 Efficient	
CERTIFICATIONS	UL Listed	
CATALOG NOTES	10 CFR Part 431 (2016) Efficient	

Physical Att	ributes
COIL MATERIAL	Copper
ENCLOSURE	NEMA
FRAME	FR942
INSULATION	220 °C
MATERIAL	Copper winding
MOUNTING	Floor or wall, upright only
TAP SIZE	2 at +2 4 at -2.5
ТУРЕ	Energy- efficien ventilate dry-type transfor
WIRING CONNECTION	280B

Specifications

Photo is representative



Eaton V48M28T7516CU

Eaton General purpose ventilated transformer, Fungus proof, CU windings, DOE 2016, NEMA 2, FR942, 220°C, 75 kVA, Floor/wall mnt upright only, 3-phase, PV: 480V delta, SV: 208Y/120, NEMA ST-20, 2 at +2.5%, 4 at -2.5%, 150°C, 75 kVA

General specifications		
PRODUCT NAME	Eaton General purpose ventilated transformer	
CATALOG NUMBER	V48M28T7516CU	
UPC	786680192012	
PRODUCT LENGTH/DEPTH	24 in	
PRODUCT HEIGHT	43 in	
PRODUCT WIDTH	30.5 in	
PRODUCT WEIGHT	632 lb	
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	
COMPLIANCES	DOE2016 Efficient	
CERTIFICATIONS	UL Listed	
CATALOG NOTES	10 CFR Part 431 (2016) Efficient	

Physical Att	ributes
COIL MATERIAL	Copper
ENCLOSURE	NEMA
FRAME	FR942
INSULATION	220 °C
MATERIAL	Copper winding
MOUNTING	Floor or wall, upright only
TAP SIZE	2 at +2 4 at -2.5
ТУРЕ	Energy- efficien ventilate dry-type transfor
WIRING CONNECTION	280B