

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



VR1031 100A 3W3P RCPT

Hubbell--Killark

Poles

Voltage Rating

Catalog Number	VR1031
Manufacturer	HubbellKillark
Description	100A 3 Pole 3 Wire Receptacle Assembly
Weight per unit	2.0 (lbs/each)
	Gen Purpose Recept & Surge Pro
Features	
amperage rating	100
Number of Wires	2

extra flex: #4-#2;Regular stranding: #4-#2

Wire Size **Dimensions and Weight**

Size 5.37 in x 4.25 in x 4.75 in

3

250:600

Descriptions

Description	100A 3W3P RCPT
extra long description	KLRK VR1031 VERSAMATE 100A 3W3P REC
Long Description	100A 3 Pole 3 Wire Receptacle Assembly
Product Type	Versamate 100A 3W3P Recpt
Special Features	VersaMate® metallic pin & sleeve plugs, receptacles, and in-line connectors are designed for heavy duty industrial use. These devices supply power to both fixed and portable electrical equipment including pumps, generators, welders, vacuums, blowers and similar apparatus. Suitable for indoor and outodoor use, as well as applications that include wet, cold, hosedown, hazardous and corrosive environments. Configurations are also available in reverse-service and polarized orientations.

Manufacturer Information

Brand	KILLARK
GTIN	00783936834832
Manufacturers Part Number	VR1031
series	VersaMate
UPC	783936834832

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Туре	Pin & Sleeve



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging Carton	1
Weight Per each	2
Uses, Certifications, and Standards	
Application	Suitable for indoor or outdoor use. Applications include the wet, cold, hosedown, hazardous or corrosive areas in such industrial applications as:Pulp & Paper Mills, Electrical Power Plants, Petrochemical Plants, Wastewater Treatment, Marine, Docks, Ports, Construction Sites, Breweries, Re?neries, Chemical Plants, Grain Facilities, Textile Manufacturing, Food Processing Facilities
environmental conditions	Wet and hazardous locations
nema rating	NEMA 3, 4, 4x
standard	UL, CSA