

CONNECTORS

Mechanical Connectors

Aluminum Service Wedge Clamps W Series



SPECIFICATIONS

- UL486A Listed for Wire Connector.
- Temperature Rating: 90 °C
- Voltage: 600V max.

FEATURES

- For dead-ending self-supporting drop wire.
- Saves conductor – drop wire may be cut to exact length.
- Can be attached to bare neutral in any point in the span.
- Adjustment in drop wire sag are easily made.
- Grips ACSR, AAAC or aluminum conductor.
- Catalog number with “FC” suffix have a Flexible bail.



| CAT. NO. | FIG. NO. | ACSR | WIRE RANGE | | LENGTH (L) | WIDTH (W) | STD. CTN. QTY. |
|----------|----------|---------|-----------------|---------|------------|-----------|----------------|
| | | | ALUMINUM | AAAC | | | |
| W62-1 | 1 | 2-6 | 1 STR-6 SOL | 2-6 | 12.000 | 2.375 | 12 |
| W62-1FC | 2 | 2-6 | 1 STR-6 SOL | 2-6 | 17.500 | FLEX | 12 |
| W20-1 | 1 | 1/0-4 | 2/0 STR-2 SOL | 1/0-4 | 12.500 | 2.375 | 8 |
| W20-1FC | 2 | 1/0-4 | 2/0 STR-2 SOL | 1/0-4 | 18.500 | FLEX | 8 |
| W40-1 | 1 | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 12.750 | 2.375 | 6 |
| W40-1FC | 2 | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 18.500 | FLEX | 6 |

CONNECTORS

Mechanical Connectors

Aluminum Service Wedge Clamps W Series



SPECIFICATIONS

- UL486A Listed for Wire Connector.
- Temperature Rating: 90 °C
- Voltage: 600V max.

FEATURES

- For dead-ending self-supporting drop wire.
- Saves conductor – drop wire may be cut to exact length.
- Can be attached to bare neutral in any point in the span.
- Adjustment in drop wire sag are easily made.
- Grips ACSR, AAAC or aluminum conductor.
- Catalog number with “FC” suffix have a Flexible bail.



| CAT. NO. | FIG. NO. | ACSR | WIRE RANGE | | LENGTH (L) | WIDTH (W) | STD. CTN. QTY. |
|----------|----------|---------|-----------------|---------|------------|-----------|----------------|
| | | | ALUMINUM | AAAC | | | |
| W62-1 | 1 | 2-6 | 1 STR-6 SOL | 2-6 | 12.000 | 2.375 | 12 |
| W62-1FC | 2 | 2-6 | 1 STR-6 SOL | 2-6 | 17.500 | FLEX | 12 |
| W20-1 | 1 | 1/0-4 | 2/0 STR-2 SOL | 1/0-4 | 12.500 | 2.375 | 8 |
| W20-1FC | 2 | 1/0-4 | 2/0 STR-2 SOL | 1/0-4 | 18.500 | FLEX | 8 |
| W40-1 | 1 | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 12.750 | 2.375 | 6 |
| W40-1FC | 2 | 4/0-2/0 | 4/0 STR-2/0 SOL | 4/0-2/0 | 18.500 | FLEX | 6 |