

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2301 East Saint Elmo Rd. Suite 105 78744-0000, TX Austin Phone: 512-443-5600

Fax: 512-443-5601



Type

WFD30LASPL Wi-Fi Smart Univ Dimmer, LT Almond *Eaton Wiring Devices*

Catalog Number	WFD30LASPL
Manufacturer	Eaton Wiring Devices
Description	Eaton Wi-Fi Smart Dimmer Switch, Residential, Flush, 120V, Back and Side Wire, Light Almond, 60HZ, Single-Pole, Multi, Single-Gang, , 450W Dimmable Led/CFL, 600W Incandescent, Halogen, Magnetic Low Voltage, Electronic Low Voltage, Used With Wacd, Wifi
Weight per unit	0.3700 (lbs/each)
Product Category	Wiring Devices
Features	
dimensions	2.2600 IN X 2.2600 IN X 6.4100 IN
Voltage Rating	120 V
Wattage	450 W (LED, CFL), 600 W (INC/HAL, ELV, MLV)
Descriptions	
Description	WI-FI SMART UNIV DIMMER, LT ALMOND
extra long description	EWD WFD30-LA-SP-L Wi-Fi Smart Univ
Features	Wi-fi smart switches, receptacles, and dimmers from Eaton set up quickly and easily with Amazon's Alexa app—no other hubs or controllers are necessary. Plus Frustration Free Setup starts the connection automatically. Schedule lights to go on and off—and even dim—to fit your daily routine. Save energy and feel more comfortable and secure. You can even add voice-control using ar Amazon Echo device.
Long Description	Eaton Wi-Fi smart dimmer switch, Residential, Flush, 120V, Back and side wire, Light Almond, 60Hz, Single-pole, Multi, Single-gang, ,450W Dimmable LED/CFL, 600W Incandescent, Halogen, Magnetic Low Voltage, Electronic Low Voltage, Used with WACD, WiFi
Product Type	Wi-Fi Smart Univ Dimmer, LT Almond
Manufacturer Information	
Brand	Eaton
GTIN	00786689366858
Manufacturers Part Number	WFD30-LA-SP-L
UPC	786689366858
Taxonomies, Classifications, and (Categories
	Residential dimmers, motion sensors, controls, & photo cells

Dimmer switch



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2301 East Saint Elmo Rd. Suite 105 78744-0000, TX Austin Phone: 512-443-5600 Fax: 512-443-5601

_		•
Pac	/ A A	\mathbf{n}
241	K AII	
uu	\u u	ши

Carton	1	
Package	36	
Weight Per each	0.37	

Uses, Certifications, and Standards

Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other
Frequency Rating	60 Hz
Operating Temperature	32 to 104 °F (0 to 40 °C)
standard	NOM,cULus Listed,California Code of Regulations Title 24