

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WLQT Wire Pulling Lubricant Gel, 1 Quart Minnesota Mining (3M)

Catalog Number	WLQT
Manufacturer	Minnesota Mining (3M)
Description	3M™ Wire Pulling Lubricant WL Is A Translucent Polymer Gel That Acts As An Excellent Lubricant For Pulling Both Electrical and Communication Cable. This Lubricant Gel Wipes Off The Cable Quickly and Cleanly Before Terminating or Splicing. The Lubricant Has A Low Coefficient Of Friction Which Lessens The Chance Of Cable Jacket Damage From High Pulling Forces.
Weight per unit	0.1947 (lbs/each)
Product Category	Paint, Chemicals, Etc.
Descriptions	
Description	WIRE PULLING LUBRICANT GEL, 1 QUART
extra long description	3M 7000058273 3M™ Wire-Pulling Lubr
Features	3M™ Wire Pulling Lubricant WL is a consistent gel that does not liquefy, or separate with hot or cold aging. It stays thick, smooth and ready to apply. Temperature range of 20 to 110 degrees F (-6.7 to 43 degrees C).
Long Description	3M™ Wire Pulling Lubricant WL is a translucent polymer gel that acts as an excellent lubricant for pulling both electrical and communication cable. This lubricant gel wipes off the cable quickly and cleanly before terminating or splicing. The lubricant has a low coefficient of friction which lessens the chance of cable jacket damage from high pulling forces.
Product Type	3M™ Wire-Pulling Lubricant WL
Special Features	Translucent White
Manufacturer Information	
Brand	3M
GTIN	00054007506225
Manufacturers Part Number	WLQT
UPC	054007506225
Taxonomies, Classifications, and G	Categories
Category Description	ADHESIVES
Туре	Gel
Packaging	
Carton	1
Package	12
Weight Per each	0.1947

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards		
Application	Lubricant	