

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WT411 Wingtwist Wire Connector, WT41 Tan, 100/Box Ideal

| Catalog Number | WT411 |
|-----------------------------|--|
| Manufacturer | Ideal |
| Description | Buchanan, Wire Connector, Wingtwist, Conductor Range: 22 - 10 Awg, 2/20 Awg Min, 3/10 Solid Awg Max, Number Of Conductors: 1 to 6, Material: Flame-Retardant Polypropelene, Color: Tan, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell Rated At 105 Deg C (221 F), Model Number: WT41 |
| Weight per unit | 0.0050 (lbs/each) |
| Product Category | Electrical Fixture Conn (Nuts |
| Features | |
| Material | Flame-retardant Polypropelene |
| Voltage Rating | 600 |
| Material, Color, and Finish | |
| Color | Tan |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| | • | | |
|-------|-----|-----------|---|
| 11000 | rın | tion | |
| Desc | , | THE STATE | • |
| | p | | • |

| scriptions | MUNICIPALICE MAINE COMMISCION MATALETANI, 400 INOV |
|------------------------|--|
| Description | WINGTWIST WIRE CONNECTOR, WT41 TAN, 100/BOX |
| extra long description | IDEAL WT41-1 WINGTWIST WT41 TAN, 10 |
| Features | With a full line for virtually every wire size and combination, the WingTwist Wire Connector offers a great combination of performance and value. The contoured wing design of the WingTwist provides maximum torque for a variety of electrical applications while the copolymer shell and live-action spring expand for smooth, progressive tightening providing dependable connections. With a tough, flame-retardant shell that withstands environmental extremes, and a long, deep skirt to provide maximum dielectric prote |
| Long Description | Buchanan, Wire Connector, WingTwist, Conductor Range: 22 - 10 AWG, 2/20 AWG Min, 3/10 Solid AWG MAX, Number Of Conductors: 1 to 6, Material: Flame-retardant Polypropelene, Color: Tan, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F), Model Number: WT41 |
| Product Type | Wingtwist WT41 Tan, 100 Box |
| Special Features | 1,000V Maximum In Fixtures And Signs; Deep, Wide-Throated Skirt Protects Against Flash-Over And Turned-Back Strands For Maximum Dielectric Protection; Features: Five Color-Coded Models Cover Common Construction Wire Ranges; Fixed, Square-Wire Spring Threads Itself Creating Secure Pressure Grip; Green Model Designed For Ground Connections; Model Number: WT41; UL 486C Listed (WGR UL 467 Listed) And CSA C22.2 #188 Certified; Unique Contoured Wing Design Acts As Built-In Wrench Providing Maximum Torque With Minimum E |
| nufacturer Information | |
| Brand | Ideal |
| | |

Ma

| Brand | ldeal | |
|---------------------------|----------------|--|
| GTIN | 00781789967660 | |
| Manufacturers Part Number | WT41-1 | |
| UPC | 781789967660 | |

Taxonomies, Classifications, and Categories

| Category | Description | WIRE NUTS |
|----------|-------------|-----------|
| | | |

Availability

| minimum qty 1 | 00 |
|---------------|----|

Packaging

| Carton | 1000 |
|-----------------|-------|
| Weight Per each | 0.005 |

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | Insulating or Joining 1 or more conductors |
|--------------------------|---|
| environmental conditions | Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 |
| | F) |
| standard | CSA C22.2 #188, UL 486C Listed, RoHS |