

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WWHR15 High Volt Rubberless Tape 30 FTX 1.5 In Nsi Industries

ManufacturerNsi IndustriesDescriptionWarriorwrap WW-HR-15 Black High-Voltage Linerless Rubber Splicing Tape Is Strong Enough For Professional Environments and Gets The Job Done Right The First Time, Every Time. This Tape Is 30MIL Thick, 1.5 Inch Wide, 30FT Long and Has An Ethylene Rubber-Based Design. The Self-Bonding Adhesive Helps Stick to Uneven Surfaces and Easily Conforms to Irregular Shapes. Ton Breaking Strength and Elasticity Make Warriorwrap An	Catalog Number	WWHR15
Splicing Tape Is Strong Enough For Professional Environments and Gets The Job Done Right The First Time, Every Time. This Tape Is 30MIL Thick, 1.5 Inch Wide, 30FT Long and Has An Ethylene Rubber-Based Design. The Self-Bonding Adhesive Helps Stick to Uneven Surfaces and Easily Conforms to Irregular Shapes.	Manufacturer	Nsi Industries
Excellent Choice For Insulating, Jacketing Of Splices On Power Cables, Jacketing Terminati	Description	Splicing Tape Is Strong Enough For Professional Environments and Gets The Job Done Right The First Time, Every Time. This Tape Is 30MIL Thick, 1.5 Inch Wide, 30FT Long and Has An Ethylene Rubber-Based Design. The Self-Bonding Adhesive Helps Stick to Uneven Surfaces and Easily Conforms to Irregular Shapes. Top Breaking Strength and Elasticity Make Warriorwrap An Excellent Choice For Insulating, Jacketing Of Splices On Power
Weight per unit 0.3870 (lbs/each)	Weight per unit	5
Product Category Markers & Marking Tapes - Tape		Markers & Marking Tapes - Tape
Features	Features	
maximum voltage 69	maximum voltage	69
Temperature Range 130 C, 266 F	Temperature Range	130 C, 266 F
Tensile Strength 333.6	Tensile Strength	333.6
Warranty 1 YEAR	Warranty	1 YEAR
Material, Color, and Finish Backing Material NSI		NSI
Dimensions and Weight	Dimensions and Weight	
Length 30	•	30
Thickness 30	Thickness	30
Width 1.5000000000000000000000000000000000000	Width	1.5000000000000



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	HIGH VOLT RUBBERLESS TAPE 30 FTX 1.5 IN
extra long description	NSI WW-HR-15 Linerless Rubber Tape
Features	Its Warrior Time. At NSI, we put our 45 years of experience in the electrical industry into WarriorWrap, electrical tape strong enough to rise to any challenge.That quality starts with strong adhesion to stick to uneven surfaces. But that's not allâ€"it also features the best breaking strength around and unmatched elasticity. This high-voltage linerless rubber splicing tape can handle the toughest jobs, like the insulation and jacketing of splices on power cables from 600-Volt up to 69,000 Volt. The self
Long Description	WarriorWrap WW-HR-15 Black High-Voltage Linerless Rubber Splicing Tape is strong enough for professional environments and gets the job done right the first time, every time. This tape is 30mil thick, 1.5 inch wide, 30ft long and has an ethylene rubber-based design. The self-bonding adhesive helps stick to uneven surfaces and easily conforms to irregular shapes. Top breaking strength and elasticity make WarriorWrap an excellent choice for insulating, jacketing of splices on power cables, jacketing terminati
Product Type	Linerless Rubber Tape HV 1.5" 30FT
Manufacturer Information	
Brand	NSi
GTIN	00662381365606
Manufacturers Part Number	WW-HR-15
UPC	662381365606
Taxonomies, Classifications, and Cat	•
Category Description	ТАРЕ
Packaging	
Carton	1
Weight Per each	0.387