

Eaton XTOE020CCS

Catalog Number: XTOE020CCS

Eaton C440 electronic overload relay, XT IEC, 4-20A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



General specifications

Product Name	Catalog Number
Eaton C440 electronic overload relay	XTOE020CCS
UPC	Product Length/Depth
786685416472	1.8 in
Product Height	Product Width
4.3 in	1.42 in
Product Weight	Compliances
0.87 lb	ATEX Compliant
	RoHS Compliant
	CE Marked

Certifications

IEC 60947
CSA Certified
EN 60947
UL Listed

Product specifications

Overload range

4-20A

Type

Electronic overload relay

Frame size

45 mm

Mounting method

Direct

Contact configuration

NO, NC

Trip type

Selectable 10 A, class 10 ,20, 30

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOE_C 3D Model Xchange

XTOE_C 2D PDF

XTOE_C 2D Drawing Xchange

XTOE_C AutoCAD 2D Footprint (mm)

XTOE_C AutoCAD 2D Footprint

XTOE_C 3D Inventor

Installation instructions

XTOE/ZEB IEC Electronic Overload - Self Powered

Specifications and datasheets

Eaton Specification Sheet - XTOE020CCS



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia

Eaton XTOE020CCS

Catalog Number: XTOE020CCS

Eaton C440 electronic overload relay, XT IEC, 4-20A overload range, 45 mm Frame size, NO-NC contact configuration, Direct to contactor mounting, Selectable - 10A, 10, 20, 30 trip type



General specifications

Product Name	Catalog Number
Eaton C440 electronic overload relay	XTOE020CCS
UPC	Product Length/Depth
786685416472	1.8 in
Product Height	Product Width
4.3 in	1.42 in
Product Weight	Compliances
0.87 lb	ATEX Compliant
	RoHS Compliant
	CE Marked

Certifications

IEC 60947
CSA Certified
EN 60947
UL Listed

Product specifications

Overload range

4-20A

Type

Electronic overload relay

Frame size

45 mm

Mounting method

Direct

Contact configuration

NO, NC

Trip type

Selectable 10 A, class 10 ,20, 30

Resources

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOE_C 3D Model Xchange

XTOE_C 2D PDF

XTOE_C 2D Drawing Xchange

XTOE_C AutoCAD 2D Footprint (mm)

XTOE_C AutoCAD 2D Footprint

XTOE_C 3D Inventor

Installation instructions

XTOE/ZEB IEC Electronic Overload - Self Powered

Specifications and datasheets

Eaton Specification Sheet - XTOE020CCS



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia