

# Specifications

## Eaton XTCEXFAG11

Contactory Accessory - Auxiliary Contact, Two-pole, Screw terminals, D-G Frame size, 1NO-1NC contact configuration, 16A conventional thermal rating, Front mounting, used with XTRE control relays



### General specifications

<b>PRODUCT NAME</b>	Eaton motor control auxiliary contact
<b>CATALOG NUMBER</b>	XTCEXFAG11
<b>UPC</b>	782116354702
<b>PRODUCT LENGTH/DEPTH</b>	1.5 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	1 in
<b>PRODUCT WEIGHT</b>	0.07 lb
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	ATEX Compliant CCC Marked CE Marked
<b>CERTIFICATIONS</b>	IEC 60947 EN 60947 UL Listed CSA Certified
<b>CATALOG NOTES</b>	Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

### Product specifications

<b>USED WITH</b>	XTRE control relays
<b>NUMBER OF POLES</b>	Two-pole
<b>TYPE</b>	Contactory Accessory - Auxiliary Contact
<b>FRAME SIZE</b>	D-G
<b>TERMINALS</b>	Screw
<b>CONTACT CONFIGURATION</b>	1 NO-1 NC
<b>MOUNTING METHOD</b>	Front
<b>CONVENTIONAL THERMAL CURRENT</b>	16A
<b>QUANTITY</b>	5

### Resources

<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - XTCEXFAG11</a>
--------------------------------------	--

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



# Specifications

## Eaton XTCEXFAG11

Contactory Accessory - Auxiliary Contact, Two-pole, Screw terminals, D-G Frame size, 1NO-1NC contact configuration, 16A conventional thermal rating, Front mounting, used with XTRE control relays



### General specifications

<b>PRODUCT NAME</b>	Eaton motor control auxiliary contact
<b>CATALOG NUMBER</b>	XTCEXFAG11
<b>UPC</b>	782116354702
<b>PRODUCT LENGTH/DEPTH</b>	1.5 in
<b>PRODUCT HEIGHT</b>	2 in
<b>PRODUCT WIDTH</b>	1 in
<b>PRODUCT WEIGHT</b>	0.07 lb
<b>WARRANTY</b>	Not Applicable
<b>COMPLIANCES</b>	ATEX Compliant CCC Marked CE Marked
<b>CERTIFICATIONS</b>	IEC 60947 EN 60947 UL Listed CSA Certified
<b>CATALOG NOTES</b>	Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.

### Product specifications

<b>USED WITH</b>	XTRE control relays
<b>NUMBER OF POLES</b>	Two-pole
<b>TYPE</b>	Contactory Accessory - Auxiliary Contact
<b>FRAME SIZE</b>	D-G
<b>TERMINALS</b>	Screw
<b>CONTACT CONFIGURATION</b>	1 NO-1 NC
<b>MOUNTING METHOD</b>	Front
<b>CONVENTIONAL THERMAL CURRENT</b>	16A
<b>QUANTITY</b>	5

### Resources

<b>SPECIFICATIONS AND DATASHEETS</b>	<a href="#">Eaton Specification Sheet - XTCEXFAG11</a>
--------------------------------------	--

---

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

---



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

