

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Packaging Carton

Package

Weight Per each

## **YGHC34C29 300-500 to 3/0-250 Ground C** *Burndy LLC*

Catalog Number	YGHC34C29
Manufacturer	Burndy LLC
Description	Copper Compression C Connector, 300-500 Kcmil (Run) & 3/0 Awg(STR) - 250 Kcmil (Tap).
Weight per unit	0.5100 (lbs/each)
Product Category	Large Terminals & Connectors
tures	
Die Index	1011
Material	Copper
scriptions	
Description	300-500 TO 3/0-250 GROUND C
extra long description	BUR YGHC34C29 300-500 TO 3/0-250 GR
Long Description	Copper Compression C Connector, 300-500 kcmil (Run) & 3/0 AWG(Str) - 250 kcmil (Tap).
Product Type	Compression
Special Features	Features: Irreversible Compression Ground Tap Figure C Connectors, Accommodates All Cable Combinations From #6 AWG Solid Through 500 KCMIL, C- Shaped Opening Permits Placing Two Continuous Parallel Cables Into Conductor Groove UL467 Listed, Acceptable For Direct Burial In Earth Or Concrete Prefilled With PENETROX Compound And Strip Sealed, Certain Sizes Are Also UL467 Listed And CSA Certified For Wire To Ground Rod, Conductor Size (tap - Mm): 95 - 120 SQ-MM, Die Index: 1011 Element A, Tools, Die Set Cata
nufacturer Information	
Brand	BURNDY
GTIN	00781810221075
Manufacturers Part Number	YGHC34C29
UPC	781810221075
conomies, Classifications, and C	Categories
Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Туре	Taps

1

15 0.51

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	For Direct Burial Cables
standard	Direct Burial